



AVN263 / 263V Outdoor H.264 Network Camera



FEATURES

- Powerful Remote Surveillance on Multiple Mobile Platforms
 - For mobile device platforms, iPad®, iPod®, iPhone®, BlackBerry®, Nokia® Symbian, Windows® Mobile & Android™ (with their built-in web browsers or EagleEyes)
 - For web browsers, Internet Explorer®, Mozilla Firefox®, Safari®, Google Chrome™ and Opera
 - For operating systems, Windows & Mac
 - For multiple device control, our CMS software, Video Viewer, is provided for free
- Smart Zoom: zoom in on the object that triggered the event
- The best cost / performance outdoor solution with IP67
- IR effective distance up to 40 meters with 56 IR LEDs
- Smart Light Control to avoid overexposure
- Excellent outdoor ID design with cable management
- Low-latency video streaming with H.264 compression format
- Free CMS software with E-Map for multiple devices control & surveillance
- Motion detection and event notification functions
- (AVN263V Only) ONVIF standard supported to simplify system integration

SPECIFICATIONS

	AVN263	AVN263V
■ Network		
Network Compression	H.264 / MPEG4 / MJPEG	
LAN Port	YES	
LAN Speed	10/100 Based-T Ethernet	
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP, IPv4, Bonjour, UPnP, DNS, UDP	
ONVIF Compatible	NO	YES
Frame Rate	NTSC: 30, PAL: 25	
Number of Online Users	10	
Security	Multiple user access levels with password protection / IP address filtering	
Web management	(1) Web browsers, such as Internet Explorer, Mozilla Firefox, Google Chrome, Safari & Opera for single device access, or (2) Free CMS software, Video Viewer, for up to 16 network cameras control simultaneously	



SPECIFICATIONS (CONTINUED)

	AVN263	AVN263V
■ Camera		
Image Sensor	1/3" HR color CCD image sensor	
Pixels	768(H) x 494(V) <NTSC> / 752(H) x 582(V)) <PAL>	
Min Illumination	0.05 Lux / F1.8, 0 Lux (IR ON)	
Shutter Speed	1 / 60 (1/50) to 1 / 100,000 sec.	
S/N Ratio	More than 48dB (AGC off)	
Lens	f4.0mm ~ f9.0mm	
Viewing Angle	75° ~ 36°	
IR LED	56 units	
IR Effective Range	Up to 40 meters	
Smart Light Control	YES	
Smart Zoom	YES	
White Balance	ATW	
AGC	Auto	
IRIS Mode	AES	
IP Rating	IP67	
Power Source (±10%)	AC100V ~ 240V	
Power Consumption (±10%)	Max. 13W	
Operating Temperature	-20°C ~ 40°C	
■ Others		
Mobile Surveillance	iPad, iPod, iPhone, BlackBerry, Windows Mobile, Symbian & Android	
Motion Detection	YES	
Event Notification	FTP / Email / SMS	
Minimum Web Browsing Requirements	<ul style="list-style-type: none"> ● Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD ● 256 MB RAM ● AGP graphics card, Direct Draw, 32MB RAM ● Windows 7, Vista & XP, DirectX 9.0 or later ● Internet Explorer 7.x or later 	

* The specifications are subject to change without notice.

** Dimensional tolerance: (± 5mm)

Dimensions

