SAMSUNG



SmartCam Full HD PoE SNH-V6430BNH



SNH-V6430BNH

Simple, Smart, Secure **SmartCam outdoor helps** you look after 24/7.

- 1080p Full HD resolution
- Weather-resistant housing (outdoor)
- Easy installation with PoE adapter
- 130° Ultra-wide angle lens
- Night vision to 15m(50ft)
- Versatile for indoor, outdoor (optional accessory kit for indoor)











130° Ultra-Wide








True Day and

Dimensions

Unit:mm (inch)



Contents

- Camera
- PoE Power adapter with plug
- LAN cable(10m/33 ft)
- 3 Screws, wall anchors
- Quick Start Guide
- General Public License(GPL)

Specifications

SNH-V6430BNH	
Video	
Imaging Device	1/3" CMOS
Effective Pixels	
	1944(H) x 1092(V)
Scanning System	Progressive
Min. Illumination	0.3Lux(Color), 0Lux(Black/White)
Lens	
Focal Length	2.8mm
Angular Field of View(H/V/D)	D:130°/H:113°/V:63°
Focus Control	Fixed Focus
Lens Distortion Correction	Support (Camera level)
Operational	
IRLED	850nm
Viewable Length	15m(50ft)
Day & Night	True D/N (Auto)
Wide Dynamic Range	HDR
Contrast Enhancement	Auto
Digital Noise Reduction	Support (2D+3D Noise Filter)
Motion Detection	Off/On
Audio Detection	Off/On
White Balance	Auto
Digital Zoom	4x(mobile), 10x(Web)
Flip/Mirror	Off/On
Memory Slot	SDXC Memory Slot (Max 128GB)
Network	
Ethernet	RJ45
Wireless	WiFi 802.11 a/b/g/n/ac (Dual Band)
Video Compression Format	H.264
Resolution	1920x1080/1280x720/640x360
Audio I/O	Built-in Mic
Audio Compression Format	G.711 u-law
IP	IPv4
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTSP, NTP, HTTP, HTTPS, SSL, DHCP, SMTP, ICMP, ARP, DNS, UPnP
Security	HTTPS(SSL) Login Authentication Digest Login Authentication
Environmental	
Operating Temperature / Humidity	-30°C ~ +40°C(-22°F ~ +104°F) / Less than 90% RH
Electrical	
Input Voltage / Current	PoE(802.3af, Class3)
Power Consumption	6.7W
Power Connector	RJ45(PoE)
Mechanical	
Color / Material	White/Plastic
Dimension (WxHxD/ΦxH)	Φ78mm×71.1mm(Φ78mm×118.6mm with bracket)
Weight	271g

