

DH-HAC-HF3220E

2.4Megapixel 1080P HDCVI Box Camera



Features

- 1/2.8" 2.4Megapixel CMOS
- 25/30fps@1080P, 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and SD switchable
- OSD Menu, control over coaxial cable
- DWDR, Day/Night(ICR), AWB, AGC, BLC, 3DNR, Auto Iris
- AC24V/DC12V


DH-HAC-HF3220E

Technical Specifications





Model	DH-HAC-HF3220EP	DH-HAC-HF3220EN
Camera		
Image Sensor	1/2.8" 2.4Megapixel CMOS	
Effective Pixels	1984(H)×1225(V)	
Electronic Shutter	1/3s~1/100,000s	
Video Frame Rate	25/30/50/60fps@720P; 25/30fps@1080P	
Synchronization	Internal	
Mini. Illumination	0.05Lux/F1.4	
Video Output	1-channel BNC HDCVI high definition video output / CVBS standard definition video output (Can switch)	
Camera Features		
Day/Night	Auto(ICR) / Color / B/W	
Noise Reduction	2D/3D	
OSD Menu	Support	
Lens		
Lens Type	Manual/Auto Iris	
Mount Type	C/CS	
Auxiliary Interface		
RS485	1	
Alarm	1 channel in/out	
Audio	1 channel in	
General		
Power Supply	AC24V±10% / DC12V±10%	
Power Consumption	Max 6W	
Working Environment	-30°C~+60°C / Less than 95%RH (no condensation)	
Transmission Distance	Over 500m via 75-3 coaxial cable	
Dimensions(W×D×H)	126mm×74.1mm×65.5mm	
Weight	0.65kg	
Material	Metal	

DH-HAC-HF3220E

Dimensions (mm)



Accessories (optional)

			
PFB110W	PFA122	PFA152	PFH610N

Dahua Technology Co., Ltd.

1199 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2014 Dahua Technology Co., Ltd.